

# 44100-L-D21

WIDE SIDE SLIP TESTER WITHOUT RELEASE PLATE



# 44100-L-D22

WIDE SIDE SLIP TESTER WITH RELEASE PLATE



\*with release plate

The 44100 side slip tester range provides optimum control of the measurement of a vehicle's slip as it passes over the plate. This operation is the first step in checking the vehicle's geometry during a roadworthiness test.

The slip value obtained is used to measure the trajectory deviation of a vehicle axle. This measurement is expressed in m/km or mm/m.


The WIDE version of the side slip tester allows vehicles with 'wide' tracks (such as camper) to pass through.

TECHNICAL DATA	44100-L-D21	44100-L-D22
Release plate	without	with
Plates	1 plate	2 plates
Plate dimension (without layer)	750 x 800 mm	750 x 1050 mm
Mat dimension	890 x 820 mm	890 x 1090 mm
Thickness	36 mm	
Pit dimension	820 x 840 mm	820 x 1115 mm
Depth	35 mm	
Displacement	± 17 mm/m (±1 mm) or ± 20 m/km	
Drive-by capacity	2000 kg	
Number of moving rollers	36	48
Connection	to the MODACQ of the roller brake tester, suspension tester and other	
Power supply	12 Vdc	
Weight	53 kg	71 kg

The extended range includes a version fitted with a release plate. This accessory frees the axle from any stresses associated with driving the vehicle before taking the measurement. This plate is positioned upstream of the measurement plate, preparing the vehicle for good measurement conditions.

## PACKAGING

Parcel 44100-L-D21 - 90 kg



Parcel 44100-L-D22 - 100 kg

