

ELECTRO-HYDRAULIC SCISSOR LIFTS



GALAXIE448PLA

4T BIG SCISSOR LIFT, SURFACE MOUNTED

The scissor lift GALAXIE448PLA features a 4t lifting capacity to raise vehicles under their wheels, with integrated hydraulic auxiliary scissor lift for wheel free lifting.

The low profile configuration allows this lift to be installed surface mounted, without any concrete works.

Thanks to its long runways (usable length 4,80 m), this lift is perfectly suitable for wheel alignment applications. Metal covers as standard supply will cover the area reserved for the turntables if their use is not required.

- Lifting capacity : 4000 kg
- Lifting capacity, auxiliary lift : 4000 kg
- Lifting/lowering times : 60/65 sec.
- Max. Height (main platforms) : 1900 mm
- Min. Height : 180 mm
- Platforms width : 660 mm
- Main platform length : 4800 mm
- Auxiliary lift platforms, Max. Height : 450 mm
- Auxiliary lift platform, length : 1445-1950 mm

The surface mounted low profile scissor lift GALAXIE448PLA is particularly suitable for high precision wheel alignment works, This lift does not require any civil engineering works.

SPECIFICATIONS	GALAXIE448PLA
Main lift capacity	4 t
Auxiliary lift, capacity	4 t
Main platforms length	4800 mm
Oil pressure	230 bars
Air pressure	6-8 bars
Power supply	400 V / 3 pH / 50 Hz / 16 A
Motor power	3.5 kW
Net weight	3020 kg
Approval	CE


SPECIFICATIONS	OPTIONS
Front turntables for wheel alignment	option
Jacking beam 2 t (ref.)	Ref. 4207420 + ACH.6228000

RELIABILITY

- All components are tested at the factory. Easy and straightforward installation procedure. Low maintenance requirements..

SAFETY

- Automatically activated mechanical latching device (in compliance with the European regulations currently in force)
- Hydraulic levelling, monitored by a photocell, without any mechanical connection between the two platforms, enabling convenient access under the lifted vehicle.
- User-friendly command unit ergonomically positioned at the ideal height, for a safe and convenient control of the lift.



PERFORMANCE

- Lifting platform length 4,80 m, enabling the reception of many light commercial vehicles, long wheelbase vehicles, sport-Utility vehicles, etc. . .
- Integrated wheel free hydraulic scissor lift, that allows all kind of technical lifting operation requiring one or more wheels to be removed.
- Lifting kit high performance with 4 LED lights 24V that can be moved and positioned in different ways to optimize underbody lighting.
- Quick raising, sturdy construction.
- Anti-rust measures : High quality paint with sealer applied at metal joints.
- High precision for wheel alignment.

