

MDP425AV2

AUTOMATIC TYRE CHANGER

- Pneumatic tilting column
- Simultaneous locking of the horizontal and vertical arm
- 41mm hexagonal vertical arm
- 50X50 mm horizontal arm
- Square turntable with 2 pneumatic cylinders of Ø 80 mm
- Third arm included and premounted in the factory (Rim press, roller, pusher and bead lifter)
- Tilted bead breaker arm with an articulated shovel at 12°
- CE-compliant inflation gun
- 2 rotation speeds



Standard accessories :

Front & rear protection inserts, lever, lube pot ring, jaw protections



Optional: see list of accessories for MDP.

CHARACTERISTICS

MDP425AV2

Inside clamping capacity	10" - 25"
Outside clamping capacity	10" - 22"
Maximum tyre width	305 mm (12")
Maximum tyre diameter	1000 mm (39")
Bead breaker force	2,8T
Operating pressure	8 - 12 bars
Power supply	400V/50Hz/3ph
Motor power	0,8 - 1,1 kW
Rotation speed	7-14 tours/min
Noise level	<70 +/- 3dB (A)
Net weight	270 kg

MULLER AUTOMOTIVE
Tél: 02 37 33 34 00
Mail: adv@mullerautomotive.fr

Site de Chartres
8, Rue Réaumur
28000 CHARTRES