

MDP627AL

LEVERLESS TYRE CHANGER

- LEVERLESS system
- Pneumatic tilting column
- Reinforced frame and column base
- Simultaneous locking of the horizontal and vertical arm
- 41mm hexagonal vertical arm
- 60X60 mm horizontal arm
- Square turntable with 2 pneumatic cylinders of Ø 80 mm
- Tecnohelp third arm included and premounted in the factory (Rim press, roller, pusher and bead lifter)
- Tilted bead breaker arm with an articulated shovel (17°)
- CE-compliant inflation gun
- Inverter from 0 à 16 tr/min



Standard accessories :

Front & rear protection inserts, lever, lube pot ring, jaw protections



Optional: see list of accessories for MDP.

CHARACTERISTICS

MDP627AL

Inside clamping capacity	12" - 27"
Outside clamping capacity	10" - 24"
Maximum tyre width	430 mm (17")
Maximum tyre diameter	1160 mm (46")
Bead breaker force	2,8T
Operating pressure	8 - 12 bars
Power supply	230V/50Hz/3ph
Motor power	1,5kW
Rotation speed	0 à 16 tours/min
Noise level	<70 +/- 3dB (A)
Net weight	285 kg

MULLER AUTOMOTIVE
Tél: 02 37 33 34 00
Mail: adv@mullerautomotive.fr

Site de Chartres
8, Rue Réaumur
28000 CHARTRES